

P825

Lima Rotativa – Cônica Invertida. Soldada acima de 6.00mm.

| | | | | | | | | | | | | | | | | | |
|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| P825 | P1.1 | P1.2 | P1.3 | P2.1 | P2.2 | P2.3 | P3.1 | P3.2 | P3.3 | P4.1 | P4.2 | P4.3 | M1.1 | M1.2 | M2.1 | M2.2 | M2.3 |
| | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| | M3.1 | M3.2 | M3.3 | M4.1 | M4.2 | K1.1 | K1.2 | K1.3 | K2.1 | K2.2 | K2.3 | K3.1 | K3.2 | K3.3 | K4.1 | K4.2 | K4.3 |
| | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| | K4.4 | K4.5 | K5.1 | K5.2 | K5.3 | N3.1 | N3.2 | N3.3 | S1.1 | S1.2 | S1.3 | S2.1 | S2.2 | S3.1 | S3.2 | S4.1 | S4.2 |
| | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| | H1.1 | H2.1 | H2.2 | H3.1 | H3.2 | H4.1 | H4.2 | | | | | | | | | | |
| ■ | ■ | ■ | ■ | ■ | ■ | ■ | | | | | | | | | | | |

P825

HM

N



DC



DORMER



P825



3.00 – 16.00

| DC | DCON MS h7 | APMX | OAL | PRFA | P825 |
|-------|------------|------|------|------|---------------------------|
| [mm] | [mm] | [mm] | [mm] | [°] | |
| 3.00 | 3 | 4 | 38 | 10° | P8253.0X3.0 ¹⁾ |
| 6.30 | 3 | 6 | 39 | 12° | P8256.3X3.0 |
| 6.00 | 6 | 8 | 50 | 10° | P8256.0X6.0 ¹⁾ |
| 9.60 | 6 | 9.5 | 55 | 16° | P8259.6X6.0 |
| 12.70 | 6 | 12.7 | 58 | 28° | P82512.7X6.0 |
| 16.00 | 6 | 19 | 64 | 18° | P82516.0X6.0 |

¹⁾ DCON MS tolerância h6